



# Viper 70

by E-TON



*Just go there!*

## Viper 70

Cherry Red  
Royal Blue  
Sunlight Yellow  
Black & Yellow

Introducing the 2008 E-TON Viper 70 four-stroke ATV. This Viper includes a 69.3cc four-stroke air-cooled engine, Automatic C.V.T. belt transmission, and a U.S. Forest Service-approved spark arrestor. The 2008 Viper 70 meets or exceeds EPA clean air requirements and is eligible for the California Green Sticker. Includes full six month limited factory warranty. Designed for riders ages 6 and up.

### Optional Accessories

- Remote stop switch
- Safety tether switch
- Hi-Flo fuel line kit
- 3" clear stone fuel filter
- Colored handlebar grips
- Tire repair kit
- E-TON safety flag
- Helmets and apparel available on the web site

ETON AMERICA.

[www.etonamerica.com](http://www.etonamerica.com)

<b>Engine</b>			
Type	Four cycle air cooled (EPA Compliant) SOHC		
Displacement	69.3cc		
Bore / Stroke	φ47.0 * 40mm		
Compression Ratio / Pressure	9.0 : 1 / .110—130psi		
Torque / BHP	4.8N ms @ 6500rpm / 6BHP		
EPA Approved	Meet or exceeds EPA clean air requirements and CA Green Sticker		
Starting	Electrical starter with kick start backup		
<b>Transmission</b>			
Type	Automatic (C.V.T. V-Belt)		
<b>Chassis</b>			
Overall Length-With-Height	1480mm / 58.3" - 850mm / 33.5" - 860mm / 33.9"		
Wheel Base	930mm / 36.1"		
Seat Height	670mm / 26.4"		
Ground Clearance	100mm / 3.94"		
Dry Weight	112kg / 247lbs		
<b>Suspension</b>			
Front	Independent A-arms with Adjustable Shocks		
Rear	Swing Arm with Adjustable Shock		
<b>Brakes</b>			
Front	Dual mechanical drum		
Rear	Hydraulic Disc		
<b>Tires</b>			
Front	16/8-7		
Rear	16/8-7		
Tire Pressure	Front	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
	Rear	Min	3.2psi / 0.23kg/cm2
		Max	4.0psi / 0.28kg/cm2
<b>Wheels</b>			
Bolt Pattern	Front	4 x 110mm (P.C.D.)	
	Rear	4 x 110mm (P.C.D.)	
<b>Carburetor</b>			
Make/Size	SW 18mm (Manual Choke)		
Main Jet	0.95mm		
Pilot Jet	0.32mm		
Air Mixture Adjustment	Back out 1½ - 1¼ turns		
Idle Speed	Idle 1700 - 1900rpm		
<b>Sprockets</b>			
Front	520x13t		
Rear	520x28t		
Chain	#520		
<b>Battery</b>			
Jell Acid (Maintenance Free)	12V-4AH/5AH - GTX5L		
Main Fuse	7Amp		
<b>Fluids</b>			
Fuel	Type	Unleaded Gasoline 89 octane	
	Volume	4.5 liters / 1.2 gal	
Engine Oil	Type	SAE 20W - 40	
	Volume	0.8 liters / 0.84 qt	
Transmission	Type	SAE 80W/90	
	Volume	120cc / 4.1 oz	
<b>Safety Features</b>			
Safety Tether Switch	Optional equipment		
Remote Stop Switch	Optional equipment		
Enclosed Foot Rest Area	Standard equipment		
Enclosed Engine compartment	Standard equipment		
<b>Carrying Capacity</b>			
Rack Capacity	Front	N/A	
	Rear	N/A	
Towing Capacity	Trailer Wgh	N/A	
	Tongue Wgh	N/A	
Maximum Rider Weight	68.2kg / 190lb		
Minimum Rider Age	6 years		

